

Code: MC16-PAC-EX-1-KIT

## ACCESS CONTROLLER **MC16-PAC-EX-1-KIT** ROGER

The MC16-PAC-EX-1-KIT access control kit is designed to support 1 door in the RACS 5 v2 ver. EX system. The kit includes a metal enclosure with a power supply and a networked access controller.



|                               |                                                                                                              |
|-------------------------------|--------------------------------------------------------------------------------------------------------------|
| Number of served transitions: | 1 (two-way)                                                                                                  |
| Support:                      | RACS 5 v2 (Roger)                                                                                            |
| Number of supported readers:  | 4 pcs                                                                                                        |
| Battery backup support:       | max. 7 Ah                                                                                                    |
| Input lines:                  | 8 pcs                                                                                                        |
| Output lines:                 | 8 pcs                                                                                                        |
| Communication:                | <ul style="list-style-type: none"> <li>• RS-485,</li> <li>• RACS 5 v2 (Roger),</li> <li>• Wiegand</li> </ul> |
| Power supply:                 | 230 V AC                                                                                                     |

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:                 | <ul style="list-style-type: none"> <li>• Metal housing</li> <li>• Power output : 1 x 0.2 A, 1 x 1.0 A</li> <li>• Power adapter : 24 V DC / 2.2 A,</li> <li>• Battery charging current : 0.3 A</li> <li>• Protection against deep discharge of the battery</li> <li>• Tamper detection - opening the enclosure</li> <li>• Place for battery - 12 V / 7 Ah</li> <li>• Integrated support in VISO EX software</li> <li>• Functions in the VISO EX system: - MSSQL database</li> <li>- work in distributed systems</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system - unlimited</li> <li>- division of the system into partitions operated by independent operators</li> <li>- tool for integration with RACS5 (API) systems</li> <li>- integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)</li> </ul> |
| Operation temp:                | 5 °C ... 40 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Permissible relative humidity: | 10 % ... 95 % (non-condensing)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Weight:                        | 3.88 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Dimensions:                    | 405 x 365 x 120 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Manufacturer / Brand:          | ROGER                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Guarantee:                     | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |