

DATA SHEET

Code: IPC-S21FAP PTZ OUTDOOR IP CAMERA **IPC-S21FAP** - 1080p 3.6 mm IMOU

The cameras of the IMOU series have been designed with special care to simplify the configuration and operation. In combination with the user friendly IMOU platform, the IMOU series devices allow anyone to create a simple and effective surveillance system.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. Camera is according to IP66 Index of Protection norm.

In addition, the camera has the function of active deterrence of intruders using a motion-activated white light LED spotlight.

Attention! The IMOU series devices do not have a WEB interface. In order to obtain optimal performance of IMOU series cameras, it is recommended to use DAHUA Micro SD memory cards.



Standard:	TCP/IP
Sensor:	1/2.9 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	3.6 mm
View angle:	86 °
Range of IR illumination:	30 m
Horizontal rotation range:	0° 355° - Rotation of the head is limited by stops
Vertical rotation range:	0 ° 90 °
Audio:	Microphone built-in,Audio transmission via network
Image compression method:	H.265 / H.264
Main stream frame rate:	25 fps @ 4 Mpx
Network protocols:	TCP, DHCP, ONVIF



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

IPC-S21FAP



DATA SHEET

Network interface:	Ethernet : 100 Mbps
WEB Server:	
Mobile phones support:	Access by a cloud (P2P) Android: Free application IMOU iOS (iPhone): Free application IMOU
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	DHCP
Web browser access ports:	-
PC client access ports:	-
Mobile client access ports:	-
Port ONVIF:	-
RTSP URL:	-
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Main features:	 Motion Detection People detection Intelligent Object Tracking Active deterrence function - LED illuminators Alarm notifications - Sending instant motion-activated alerts to mobile phone D-ZOOM - Digital Zoom : 16x Full Color - colorful night mode LED Floodlight Light alarm Active deterrence function IMOU Cloud RESET button
Power supply:	PoE (802.3af)
Power consumption:	< 6.2 W
"Index of Protection":	IP66
Weight:	0.41 kg
Dimensions:	136 x 144 x 110 mm (with bracket)
Supported languages:	-
Manufacturer / Brand:	DAHUA / IMOU
Guarantee:	2 years



IPC-S21FAP