

Code: BCS-L-TIP14FSR3-W

## IP CAMERA **BCS-L-TIP14FSR3-W** Wi-Fi - 3.7 Mpx 2.8 mm BCS Line

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 4 MPx.

The Wi-Fi module used in the device allows the device to operate also in places with limited wiring possibilities.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).



Standard:	TCP/IP
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	3.7 Mpx
Resolution:	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens:	2.8 mm, F2.0
View angle:	<ul style="list-style-type: none"> <li>• 90 ° (manufacturer data)</li> <li>• 89 ° (our tests result)</li> </ul>
Range of IR illumination:	30 m
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Alarm inputs / outputs:	—
Audio:	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Noise reduction</li> <li>• Audio detection</li> </ul>



# DATA SHEET

Main stream frame rate:	<ul style="list-style-type: none"><li>• 20 fps @ 3.7 Mpx</li><li>• 25 fps @ 3 Mpx</li></ul>
Network interface:	10/100 Base-T (RJ-45), 2.4 GHz Wi-Fi IEEE 802.11 b/g/n
Network protocols:	IPv4, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, DHCP, DNS, NTP, Multicast, RTMP
WEB Server:	Built-in, NVR compliance, 20 on-line users
ONVIF:	21.06
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support:	Access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: <a href="#">BCS Manager</a> free application</li><li>• iOS (iPhone): <a href="#">BCS Manager</a> free application</li></ul>
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	DHCP
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features:	<ul style="list-style-type: none"><li>• Wi-Fi Module - 2.4 GHz IEEE 802.11 b/g/n ; Antenna - SMA socket</li><li>• D-WDR - Wide Dynamic Range</li><li>• 3D-DNR - Digital Noise Reduction</li><li>• ROI - improve the quality of selected parts of image</li><li>• BLC/HLC - Back Light / High Light Compensation</li><li>• D-ZOOM - Digital Zoom 16 x</li><li>• Mirror - Mirror image</li><li>• Day/night mode</li><li>• ICR - Movable InfraRed filter</li><li>• Auto White Balance</li><li>• AGC - Automatic Gain Control</li><li>• Configurable Privacy Zones</li><li>• Motion Detection</li><li>• Human detection</li></ul>
Housing:	Compact - Metal
Color:	White
"Index of Protection":	IP67
Power supply:	12 V DC / 350 mA
Power consumption:	max. 4.1 W
Operation temp:	-40 °C ... 60 °C
Weight:	0.48 kg
Dimensions:	Ø 70 x 166 mm
Supported languages:	Polish, English



# DATA SHEET

---

Manufacturer / Brand:	BCS Line
Guarantee:	<b>3 years</b>