

Code: DS-KV8213-WME1(C)/SU

WIRELESS VIDEO DOORPHONE **DS-KV8213-WME1(C)/SU** Wi-Fi / IP Hikvision

Wi-Fi / IP video doorphone is dedicated to work with II generation IP Hikvision internal panels.

Video Doorphone is mounted in a surface housing.



Sensor:	2 Mpx
Resolution:	1920 x 1080
Camera view angle:	124 °
IR illuminator:	✓
LED illuminator:	—
PIR detector:	—
Doorbell button:	2 pcs
proximity reader built-in:	13.56 MHz S50
Wireless transmission range:	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard:	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n
Network interface:	• Ethernet • Wi-Fi
RS-485 interface:	✓
Video output:	—



DATA SHEET

Video format:	H.264
Supported audio formats:	G.711
Alarm inputs:	4 pcs
Main features:	• WDR - Wide Dynamic Range • Bidirectional communication, • Noise and echo reduction • Full support via network : WiFi / LAN, • 2000 indexed users • Memory of 10 000 RFID cards • Output button support max. 2 • Lock control : 2 • Door status detection : 2 • Tamper detection - removing from mounting surface • Video Doorphone is mounted in a surface housing • IK rating : IK08
Power supply:	• PoE (802.3af) • 12 V DC / 830 mA (max)
Power consumption:	< 10 W (operation)
Housing:	Aluminum + Plastic, Protects against weather conditions
Mount:	Surface-mounted
Color:	Black + Gray
"Index of Protection":	IP65
Operation temp:	-40 °C ... 53 °C
Weight:	0.38 kg
Dimensions:	174 x 91 x 30 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Turkish, Ukrainian, Hungarian, Vietnamese, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305303882
Guarantee:	3 years