

Code: MC16-PAC-ST-5

## ACCESS CONTROLLER MODULE **MC16-PAC-ST-5** ROGER

The MC16-PAC-ST-5 controller is a multifunctional electronic module, intended for use in the RACS 5 v2 system, which enables the implementation of access control of the transition and building automation.



|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of served transitions:  | 5 (two-way)                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Number of supported readers:   | 20                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Number of users:               | unlimited (purchase of the appropriate license required)                                                                                                                                                                                                                                                                                                                                                                                |
| Number of media per ID:        | 8 - Proximity card, PIN code, fingerprint, etc.                                                                                                                                                                                                                                                                                                                                                                                         |
| Buffer memory:                 | 8 000 000 events buffer                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Number of access zones:        | 10                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Number of alarm zones:         | 10                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Battery backup support:        | 12 V / 7 Ah                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Communication:                 | <ul style="list-style-type: none"> <li>• Ethernet - RJ-45 socket</li> <li>• RACS 5 v2 (Roger)</li> <li>• RS-485 interface</li> </ul>                                                                                                                                                                                                                                                                                                    |
| Main features:                 | <ul style="list-style-type: none"> <li>• Integrated support in VISO ST software</li> <li>• Functions in the VISO ST system: <ul style="list-style-type: none"> <li>- MSSQL database</li> <li>- work in distributed systems</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system : 128</li> </ul> </li> </ul> |
| Power supply:                  | <ul style="list-style-type: none"> <li>• 17 ... 22 V AC</li> <li>• 10 ... 15 V DC</li> <li>• 22 ... 26 V DC</li> </ul>                                                                                                                                                                                                                                                                                                                  |
| Operation temp:                | 5 °C ... 40 °C                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Permissible relative humidity: | 10 % ... 95 % (non-condensing)                                                                                                                                                                                                                                                                                                                                                                                                          |



## DATA SHEET

|                       |                  |
|-----------------------|------------------|
| Weight:               | 0.14 kg          |
| Dimensions:           | 175 x 72 x 30 mm |
| Manufacturer / Brand: | ROGER            |
| Guarantee:            | <b>3 years</b>   |