

Code: PFS3110-8ET1GT1GF-96

SWITCH POE **PFS3110-8ET1GT1GF-96** 8-PORT SFP DAHUA

The device is perfect to build a network of IP cameras with power supply in the PoE 802.3af / 802.3at standard.



LAN ports:	• 8 x RJ45 10/100 Base-T (1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at)), • 1 x RJ45 10/100/1000 Base-T - Uplink, • 1 x Port SFP 1000 Base-X - Uplink
Management:	—
LED diodes:	Power, PoE, Link/Act, Uplink 1, Uplink 2
Transmission speed:	10 / 100 Mbps : 8 LAN & PoE ports , 10 / 100 / 1000 Mbps : 1 Port RJ45 (Uplink) , 1000 Mbps : 1 Port SFP (Uplink)
Maximal output power:	• 90 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 8 ports
Maximal total power:	96 W
MAC addresses table:	8k
Operation modes:	• Extend On : 250 m, 10 Mbps • Extend Off : 100 m, 100 Mbps • PD Alive
Main features:	• PoE power mode - The device supports 8-pin power supply • Ports marked in red support IEEE802.3af, IEEE802.3at, IEEE802.3bt and Hi-PoE standards with a maximum output power of 90 W per port - designed to power high power devices • Intelligent PoE power management - the device controls power consumption on individual ports • PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • protection against lightning discharges and voltage differences and strokes between devices • Industrial wide temperature design.
Certificates:	CE, FCC
Housing:	Desktop, Metal



DATA SHEET

Power supply:	53 V DC / 1.81 A (power adapter included)
Operation temp:	-10 °C ... 55 °C
Weight:	0.58 kg
Dimensions:	240 x 105 x 28 mm
Manufacturer / Brand:	DAHUA
Guarantee:	5 years