

Code: TPC-DF1241-B3F4-S2

## IP HYBRID THERMAL IMAGING CAMERA **TPC-DF1241-B3F4-S2** 3.5 mm - 960p, 4 mm - 4 Mpx DAHUA

The TPC-DF1241-B3F4-S2 Dual Thermal Imaging Camera is a modern solution that allows to detect the presence of people, animals and vehicles regardless of the prevailing vision conditions. The device is equipped with sensitive VOx microbolometer that allows to observe the objects in fog, smoke and in the absence of illumination. An additional advantage of the TPC series cameras is the ability to detect fire and send a signal to the alarm control panel when it occurs.



|                             |                                                                          |
|-----------------------------|--------------------------------------------------------------------------|
| Sensor:                     | Uncooled VOx microbolometer                                              |
| Matrix size:                | 256 x 192 px                                                             |
| Pixel pitch:                | 12 µm                                                                    |
| Thermal sensitivity (NETD): | < 50 mK @ F1.0                                                           |
| Spectral range:             | 8 µm ... 14 µm                                                           |
| Color palettes:             | 18                                                                       |
| Lens:                       | 3.5 mm                                                                   |
| View angle:                 | 51 °                                                                     |
| Digital zoom:               | x 16                                                                     |
| Resolution:                 | 1280 x 960 - 960p ,<br>1024 x 768 px ,<br>640 x 480 px ,<br>256 x 192 px |

### VIDEO CAMERA:

|              |                               |
|--------------|-------------------------------|
| Sensor:      | 1/2.7 " Progressive Scan CMOS |
| Matrix size: | 4 Mpx                         |
| Lens:        | 4 mm                          |



# DATA SHEET

|                           |                                                                                   |
|---------------------------|-----------------------------------------------------------------------------------|
| View angle:               | 71 °                                                                              |
| Min. illumination:        | 0.05 Lux (color)<br>0.005 Lux (B/W)                                               |
| Range of IR illumination: | 30 m                                                                              |
| Resolution:               | 2336 x 1752 - 4 Mpx<br>1920 x 1080 - 1080p<br>1280 x 720 - 720p<br>704 x 576 - D1 |

## General information:

|                                |                                                                                                                                                                                 |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                      | TCP/IP                                                                                                                                                                          |
| Video output:                  | —                                                                                                                                                                               |
| RS-485 interface:              | ✓                                                                                                                                                                               |
| Memory card slot:              | Micro SD memory cards up to 256GB support (possible local recording)                                                                                                            |
| Image compression method:      | H.265 / H.264 / MJPEG                                                                                                                                                           |
| Alarm inputs / outputs:        | 1 / 1                                                                                                                                                                           |
| Audio:                         | <ul style="list-style-type: none"><li>• External microphone input</li><li>• Audio output</li><li>• Compliance with the AAC standard</li></ul>                                   |
| Main stream frame rate:        | 25 fps @ 1280 x 960<br>25 fps @ 4 Mpx                                                                                                                                           |
| Network interface:             | 10/100 Base-T (RJ-45)                                                                                                                                                           |
| Network protocols:             | HTTP, HTTPS, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/IPv6, SNMP, QoS, UPnP, NTP                                                                 |
| WEB Server:                    | Built-in, NVR compliance                                                                                                                                                        |
| Max. number of on-line users:  | 10                                                                                                                                                                              |
| ONVIF:                         | ✓                                                                                                                                                                               |
| Default IP address:            | 192.168.1.108                                                                                                                                                                   |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start                                                                                                        |
| Web browser access ports:      | 80, 37777                                                                                                                                                                       |
| PC client access ports:        | 37777                                                                                                                                                                           |
| Port ONVIF:                    | 80                                                                                                                                                                              |
| RTSP URL:                      | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream |

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:         | <ul style="list-style-type: none"> <li>• The possibility of overlapping the image from a thermal imaging camera in a classic image</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• PIP - Picture In Picture</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> <li>• Motion Detection</li> <li>• Detection of people smoking cigarettes</li> <li>• Detection of telephone conversations</li> <li>• IVS analysis : crossing the line (tripwire), intrusion, fire detection, classification of people and vehicles - The IVS analysis functions can be defined independently for the thermal imaging camera and the vision camera</li> </ul> |
| Power supply:          | <ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 1.1 A</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Power consumption:     | ≤ 13 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Housing:               | Dome - Metal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Color:                 | White                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| "Index of Protection": | IP67                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Operation temp:        | -30 °C ... 50 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Dimensions:            | Ø 122 x 112 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Weight:                | 0.77 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Supported languages:   | English, French, Spanish, Italian                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Manufacturer / Brand:  | DAHUA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Guarantee:             | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |