

Code: APTI-H50C21-36W

AHD, HD-CVI, HD-TVI CAMERA **APTI-H50C21-36W** 2Mpx / 5Mpx 3.6 mm

Megapixel camera with 1/3" CMOS sensor and AHD / HD-CVI / HD-TVI.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image. Camera is according to IP67 Index of Protection norm.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.

Attention! The camera is factory set to the resolution 2 Mpx (1080p).



Standard:	AHD, HD-CVI, HD-TVI
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	5 Mpx
Resolution:	• 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25, 30 fps, • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25, 30 fps
Lens:	3.6 mm
View angle:	• 77 ° (manufacturer data) • 70 ° (our tests result)
Range of IR illumination:	30 m
IR illuminator power adjustment:	Automatic
Video output:	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI
Audio:	—
OSD menu:	✓

Main features:	• D-WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines
Power supply:	12 V DC / 220 mA
Power consumption:	≤ 2.6 W
Housing:	Compact - Aluminum
Color:	White
"Index of Protection":	IP67
Operation temp:	-20 °C ... 60 °C
Weight:	0.39 kg
Dimensions:	172 x 73 x 73 mm
Supported languages:	Polish, English, French, Spanish, Portuguese, Russian, Italian
Manufacturer / Brand:	APTi
Guarantee:	2 years

