

Code: GENIUS-VEGA/BUS

PHOTOCELL **GENIUS-VEGA/BUS** TXRX SET FAAC

Photocells are designed for cooperation with gate automation systems. The GENIUS-VEGA/BUS photocells have a self-aligning function. The set includes transmitter and receiver.

An infra-red beam is sent to the receiver from the transmitter. If an object appears in the field of the created barrier (eg a car or a man), the photocell will react by sending a signal to change the state at the control unit input.

The devices are resistant to moisture penetration, equipped with a housing that protects against unwanted exposure to sunlight.



Beam width:	$\pm 7^\circ @ 15 \text{ m}$, $\pm 13^\circ @ 5 \text{ m}$
Operation range:	15 m
Response time:	20 ms
Power supply:	24 V DC - Control panel BUS (G-Way)
Current consumption:	• 10 mA Transmitter • 10 mA Receiver
Main features:	• Cooperation with the GENIUS gate automation system • Possibility to install up to 16 pairs of photocells on the same automation system • Self-aligning function • Modulated Infra-Red stream • Compactness tool • Surface/column mounting • Immunity to environmental changes • EN 12453 compliance - D type - Category 3
Housing:	Plastic
"Index of Protection":	IP54
Color:	Black



DATA SHEET

Operation temp:	-20 °C ... 55 °C
Weight:	0.042 kg Transmitter / Receiver
Dimensions:	105 x 35 x 25 mm Transmitter / Receiver
Manufacturer / Brand:	FAAC / GENIUS
Guarantee:	2 years