

Code: DS-K1T341AM-S

ACCESS CONTROLLER WITH FACE RECOGNITION **DS-K1T341AM-S** - 720p Hikvision

Access controller with face recognition function. The device also has functions that allow to register working time.



Sensor:	CMOS
Matrix size:	2 Mpx
Resolution:	1280 x 720 - 720p

Access control:

Cards support:	13.56 MHz S50
Face recognition distance:	0.3 m ... 1.5 m
Memory:	• Memory of 1500 face templates • Memory of 1500 RFID cards • Non-volatile log buffer of the last 150 000 events

General information:

Standard:	TCP/IP
IR illuminator:	—
LED illuminator:	—
Video output:	—



DATA SHEET

RS-485 interface:	✓
Memory card slot:	—
Alarm inputs / outputs:	—
Audio:	Speaker built-in
Network interface:	10/100/1000 Mbps (RJ-45)
Network protocols:	TCP/IP, ISUP, ISAPI
WEB Server:	Built-in
ONVIF:	—
Default IP address:	192.168.1.64
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80
PC client access ports:	port 8000
Main features:	• 4.3 " capacitive touch screen • Mechanical tamper protection • WDR - Wide Dynamic Range • AI detection : Face recognition • Configuration and management from the iVMS-4200 application • Port USB • Recording of information about Time&Attendance • Possibility to open the gate using a QR code • Door lock control output • Possibility to connect an exit button and a reed switch to control the door status
Power supply:	12 V DC / 2 A (power adapter included)
Power consumption:	≤ 24 W
Housing:	Metal
Color:	Black / Silver
"Index of Protection":	—
Operation temp:	-30 °C ... 60 °C
Weight:	0.31 kg
Dimensions:	173 x 83 x 23 mm (without bracket)
Supported languages:	English, German, French, Polish, Czech, Hungarian, Bulgarian, Serbian, Slovenian, Albanian
Manufacturer / Brand:	Hikvision
SAP Code:	302917454
Guarantee:	3 years