

DATA SHEET

Code: VM-T215M

TOUCH SCREEN MONITOR VGA, HDMI, AUDIO VM-T215M 21.5 " VILUX

The VM-T215M professional CCTV monitor is equipped with a solid metal housing and a 21.5" capacitive touch screen with a resolution of Full HD. The monitor is equipped with 2 mounting systems: mounting in the VESA standard and a set of frames enabling aesthetic, internal flush mounting of the screen in the housing of a larger device, advertising wall, interactive information terminal, etc.

The control keys are placed outside of monitor working area. This solution allows to place the monitor inside housing to protect it against change any settings by other people.

The device is designed to continuous work in closed spaces.

Attention! The touch function does not allow cooperation with recorders.



Screen size:	21.5 "
Native resolution:	1920 x 1080 px
Aspect ratios:	16:9
Matrix type:	TFT-LCD color matrix, LED backlight, Matte matrix
Supported standards:	PAL/NTSC
Contrast:	1000 : 1
Brightness:	250 cd/m ²
Viewable angles:	175 ° horizontal 175 ° vertical
Response time:	5 ms
Speakers built-in:	✓
Signal connectors:	1x VGA 1x HDMI Audio: 1x Jack (for VGA) 1 x USB - touch screen
Housing type:	Metal





DATA SHEET

Monitor mounting standard:	VESA 75, VESA 100
Power supply:	12 V DC / 3 A (power adapter included)
Power consumption:	max. 36 W
Monitor control:	OSD - by monitor control keys
Main features:	 capacitive touch screen, The set includes a set of frames for aesthetic, internal flush mounting of the screen
Operation temp:	5 °C 40 °C
Weight:	4.73 kg
Dimensions:	533 x 326 x 47 mm
Supported languages:	English
Manufacturer / Brand:	VILUX
Guarantee:	2 years