

## DATA SHEET

Code: DS-7608NXI-K1/ALARM4+1

## NVR DS-7608NXI-K1/ALARM4+1 8 CHANNELS ACUSENSE Hikvision



 $\ensuremath{\mathsf{NVR}}$  equipped with advanced functions of intelligent image analysis.

Standard:	TCP/IP
Supported resolutions:	max. 12 Mpx - 4000 x 3000 px
Video outputs:	1 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output
Audio support:	8 Channels - Audio from cameras     Bi-directional audio streaming support
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Supported hard drives:	1 x 10 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
Network protocols:	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS, ONVIF
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function Records playback from max. 8 channels in the same time
Bitrate:	max. 80 Mbps
Network functions:	Live image view, Playback the records, Backup the records     max. 128 on-line users - iVMS-4200 application
ONVIF:	<b>✓</b>



## DATA SHEET

Mobile phones support:	Port no.: 8000 or access by a cloud (P2P)  • Android: Free application Hik-Connect  • iOS: Free application Hik-Connect
Default IP address:	192.168.1.64
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 8000
PC client access ports:	8000
Mobile client access ports:	8000
RTSP URL:	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs:	4/1
PTZ control:	~
Motion Detection:	~
Intelligent Image Analysis:	~
Main features:	<ul> <li>Smart motion detection (with recognizing people and vehicles)</li> <li>Filtering of false alarms based on the recognition of persons and vehicles</li> <li>face detection</li> <li>Comparison of faces with images from the database</li> <li>Support for up to 16 face databases, including 20 000 face images</li> <li>Smart search for a person based on a face photo</li> <li>NVR from the AcuSense series</li> </ul>
USB:	2 pcs USB 2.0
Mouse support:	~
IR remote controller in the set:	-
Power supply:	12 V DC / 1.5 A (power adapter included)
Weight:	1.15 kg
Dimensions:	315 x 245 x 48 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	Hikvision
SAP Code:	303616139
Guarantee:	3 years