

Code: DS-3E1106HP-EI

SWITCH POE **DS-3E1106HP-EI** 4-PORT Hikvision

The DS-3E1106HP-EI PoE Switch ensuring smooth network transmission at the speed 10 / 100 Mbps.

4 ports support the Power over Ethernet (PoE) function. When the Extend function is enabled the PoE range increases up to 300m and the transmission speed reduces to 10 Mb/s.



LAN ports:	• 4 x RJ45 10/100 Base-TX (1 x Hi-PoE (802.3af/at/bt) + 3 x PoE (802.3af/at)), • 2 x RJ45 10/100 Base-TX - Uplink
Transmission speed:	• 10 / 100 Mbps - 4 LAN & PoE ports, • 10 / 100 Mbps - 2 Uplink ports
Maximal output power:	• 60 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 4 ports
Maximal total power:	60 W
MAC addresses table:	2k
Management:	✓
Default IP address:	192.168.1.64
Default admin user / password:	admin / -
Operation modes:	• Extend On : 300 m, 10 Mbps • Extend Off : 100 m, 100 Mbps
Main features:	• The device supports 8-pin power supply - wires : 1-2(-), 3-6(+), 4-5(+), 7-8(-) • Endspan mode support - wires : 1-2(-), 3-6(+) • Midspan mode support - wires : 4-5(+), 7-8(-) • High priority ports : 1, 2 • Configuration and management from the iVMS-4200 application • View topology and network status • Data Flow Control • Alarm notifications • Remote update of software • System logs • Possibility to mount to the wall
LED diodes:	Power, Link/Act, PoE, PoE Max, 5 Uplink, 6 Uplink
Certificates:	CE, FCC, RoHS



DATA SHEET

Housing:	Desktop, Metal
Protections:	Overvoltage 6 kV - PoE ports
Power supply:	48 V DC / 1.35 A (power adapter included)
Power consumption:	max. 65 W
Operation temp:	-10 °C ... 55 °C
Weight:	0.24 kg
Dimensions:	145 x 69 x 26 mm
Manufacturer / Brand:	Hikvision
SAP Code:	301802043
Guarantee:	3 years

