

Code: APTI-H51V21-36W

AHD, HD-CVI, HD-TVI CAMERA **APTI-H51V21-36W** 2Mpx / 5Mpx 3.6 mm

Megapixel camera with 1/3" CMOS sensor and AHD / HD-CVI / HD-TVI.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.

Attention! The camera is factory set to the resolution 2 Mpx (1080p).



Standard:	AHD, HD-CVI, HD-TVI
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	5 Mpx
Resolution:	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI @ 30 fps, 25 fps, 15 fps , 2560 x 1440 - 4 Mpx @ HD-CVI @ 30 fps, 25 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps
Range of IR illumination:	20 m
IR illuminator power adjustment:	Automatic
Lens:	3.6 mm
View angle:	• 77 ° (manufacturer data) • 70 ° (our tests result)
Video output:	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch
OSD menu:	✓

Main features:	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines • Coaxial audio - HD-TVI only
Housing:	Dome - Metal
Color:	White
Vandal-proof:	—
"Index of Protection":	IP67
Power supply:	12 V DC / 250 mA
Power consumption:	≤ 3 W
Operation temp:	-20 °C ... 60 °C
Weight:	0.42 kg
Dimensions:	Ø 97 x 91 mm
Supported languages:	Polish, English
Manufacturer / Brand:	APTI
Guarantee:	2 years