

Code: AT-UPS3000R-RACK

UPS **AT-UPS3000R-RACK** 3000 VA EAST

The AT-UPS3000R-RACK UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The device is mounted to RACK 19" cabinet.

The line-interactive power supplies analyse the voltage, frequency and phase shift angle on a current basis, and filter the voltage transmitted to the connected devices. When a mains failure is detected, the UPS immediately switches to autonomous operation mode and continues to power the equipment using the energy accumulated in internal batteries.



Power adapter type:	Line-interactive
Nominal power:	2400 W
Apparent Power:	3000 VA
Input voltage:	• 70 ... 150 V AC • 145 ... 300 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	• 100 / 110 / 115 / 120 V AC $\pm$ 5 % (Pure Sine Wave) • 200 / 220 / 230 / 240 V AC $\pm$ 5 % (Pure Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 0.3 Hz
Voltage adjustment:	✓
Frequency adjustment:	✓
Transfer time:	$\leq$ 10 ms
Battery:	4 x 12V/9Ah
Number of outputs:	6 pcs IEC320 C13

Protections:	• Glass Fuse • Overload • Short-circuit • Discharge • Overcharge • Temperature • Ethernet filter
Additional protection:	RJ45
Operation state indication:	• Large, readable LCD display with backlight : Voltage, Current frequency, Work load, Battery charge level, Temperature, Fan status, • LED indicators displaying the device's operating status : Operation modes - On-Line / Battery / Bypass, Error, • Sound signaling
Main features:	• Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • "Cold Start" function • Remote management • Excellent microprocessor control guarantees high reliability • UPS auto diagnostic system • Battery charge and maintenance control • Automatic battery charging in OFF mode • Port USB - Access from PC • SNMP - Option • Power-saving mode (selectable in the menu)
Application:	• Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Rack/Tower 2-in-1 Design
Operation temp. / Relative humidity:	5 °C ... 40 °C ≤ 93 % (non-condensing)
Weight:	26.2 kg
Dimensions:	440 x 133 x 405 mm ; RACK 19", 3U
Manufacturer / Brand:	EAST
Guarantee:	2 years