

Code: RG-S2915-24GT4MS-P-L

SWITCH POE **RG-S2915-24GT4MS-P-L** 24-PORT RUIJIE

Due to the reliability and ensuring high quality of transmission, the RG-S2915-24GT4MS-P-L 24-port PoE switch is an ideal solution for applications in CCTV IP installations. 24 ports support the Power over Ethernet (PoE) function.



LAN ports:	• 24 x RJ45 10/100/1000 Base-T (24 x PoE (802.3af/at)), • 4 x port SFP - Uplink • 1 x RJ45 - Configuration possibility from PC, • 1 x USB - Configuration possibility from PC
Management:	✓
Number of fan coolers:	2
Transmission speed:	• 10/100/1000 Mbps : 24 LAN & PoE ports Uplink ports • 100/1000/2500 Mbps - 4 x SFP ports
Maximal total power:	370 W
Switching performance:	68 Gb/s
Packet redirection speed:	51 Mpps
MAC addresses table:	16k
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Main features:	• Can be mounted in a Rack cabinet • Switch is managed through the web and the cloud (Ruijie Reyee application) • Access Control List - ACL package filtering based on source and destination IP addresses • IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs • DHCP client • BPDU Filtering/Guard • Loop back detection • Spanning Tree STP/RSTP • Errdisable Recovery • IGMP Snooping V1/V2/V3 • DHCP snooping support • Port mirroring function • Loop Protection • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200.000 h
Certificates:	CE, RoHS

Protections:	Protection against lightning discharges : 10 kV
Housing:	Desktop, Metal
Power supply:	100 V ... 240 AC
Power consumption:	≤ 403 W
Operation temp:	0 °C ... 45 °C
Weight:	3.04 kg
Dimensions:	442 x 222 x 44 mm
Manufacturer / Brand:	RUIJIE
Guarantee:	3 years