

Code: RG-RAP6262(G)

ACCESS POINT **RG-RAP6262(G)** Wi-Fi 6 2.4 GHz, 5 GHz 574 Mbps + 1201 Mbps REYEE

The RG-RAP6262(G) access point broadcasts 2 separate wireless networks in the 5 GHz band with speed 1201 Mb/s and in the 2.4 GHz band with speed 574 Mb/s. The Access Point is designed for outdoor use, ensuring good connectivity in extreme weather environments over longer distances.

Device allows to secure data transmission using the encryption protocols: WPA-PSK/WPA2-PSK/WPA-WPA2-PSK.

The product meets the IP68 tightness class.



Frequency range:	2.4 GHz, 5 GHz
Antenna type:	2x2 MU-MIMO, 2.4 GHz - 3 dBi / 5 GHz - 4 dBi, Integrated - 4 x Omnidirectional antenna
Standards:	IEEE 802.11 a/b/g/n/ac/ax
Baud rates:	2.4 GHz : max. 574 Mbps + 5 GHz : max. 1201 Mbps
Protections:	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK
LAN ports:	2 x 10/100/1000 Mbps
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Management interface:	Web browser, Ruijie Cloud
Default IP address:	10.44.77.254
Transmitter power:	≤ 26 dBm @ 2.4 GHz ≤ 25 dBm @ 5 GHz
Housing:	Outdoor, plastic (Weatherproof)
Overvoltage protection:	4 kV lightning
Power supply PoE:	✓
Power supply:	• PoE (802.3at) • 12 V / 1.5 A (power adapter not included)
Power consumption:	≤ 18 W
Operation temp:	-30 °C ... 65 °C
Permissible relative humidity:	0 % ... 100 %
Certificates:	CE, RoHS

Main features:	• Access Point is managed through the web and the cloud (Ruijie Reyee application) • Mobile phones support • Number of users : 256 (max) • Multi-SSID (max. 8) • Enable/Disable Wireless Radio • WMM (Wi-Fi Multimedia) • Transmit power control • Support for Reyee Mesh technology • Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source • Load balance • Rate limit • Wireless Network Schedule • Wireless transmission statistics • Access control • MAC addresses filtering • Wireless isolation between clients • SSID to VLAN mapping • Remote management • RESET button • LED indication • Power supply PoE • Easy to install on any wall or pole (mounting kit included)
"Index of Protection":	IP68
Weight:	1.6 kg
Dimensions:	380 x 230 x 195 mm (without mounting kit)
Pole diameters range:	Ø 70 ... Ø 140 mm
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	3 years