

## DATA SHEET

Code: RG-M18

## ACCESS POINT +ROUTER $\mathbf{RG} extbf{-M18}$ Wi-Fi 6, 2.4 GHz, 5 GHz, 547 Mbps + 1201 Mbps REYEE

With 1201 Mbps wireless speeds over the crystal clear 5 GHz band and 574 Mbps over the 2.4 GHz band, RG-M18 offers you the flexibility of 2 dedicated networks and ensures amazing wireless performance. Simple tasks such as sending e-mails or web browsing can be handled by the 2.4 GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5 GHz band – all at the same time.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes. Thanks to the advanced Reyee Mesh technology, devices are automatically switched when moving around the house.

Supports 802.11ax standard - the next generation of Wi-Fi. The high performance of the Wi-Fi 6 ensures more connected devices and faster speeds.



| Frequency range: | • 2.4 GHz,<br>• 5 GHz ,  |
|------------------|--|
| Antenna type:    | 2x2 MU-MIMO - built-in • 4 dBi @ 2.4 GHz - 2 pcs • 6.8 dBi @ 5 GHz - 2 pcs |
| Standards:       | IEEE 802.11ax Wi-Fi 6  |
| Baud rates:      | 547 Mbps @ 2.4 GHz + 1201 Mbps @ 5 GHz                                     |
| LAN ports:       | 2 x 10 / 100 / 1000 Mbps - RJ45  |
| WAN interface:   | 1 x 10 / 100 / 1000 Mbps - RJ45  |
| Port USB:        | 1  |
| LED indicators:  | Power / System / Mesh, Signal indicator                                    |
| DDNS:            | _  |
| DHCP server:     | <b>→</b>   |
| Firmware update: | <b>→</b>   |





## DATA SHEET

| Protections:  Operation modes:  Management interface: | WPA/WPA2     Black list     parental control     SSID hiding     Firewall      Repeater     Router     Access Point     WISP      Configuration using the Ruijie Reyee application     Remote management     Web browser   |
|---|--|
| Mobile phones support:                                | Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee   |
| Default IP address:                                   | 192.168.110.1  |
| Transmitter power:                                    | max. 20 dBm @ 2.4 GHz<br>max. 27 dBm @ 5 GHz   |
| Main features:  | Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments     OFDMA     Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source     MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network     Load balance     WLAN: max. 6 x BSSID     IPv4/IPv6 - Static routing     PPPoE     IPTV     WMM support (QoS mechanism of the 802.11e standard)     VPN support: PPTP VPN Server / Client     Guest Network - a separate and secure network for guests     Support for Reyee Mesh technology     System logs     RESET button     MESH button |
| Housing:  | Plastic  |
| Power supply PoE:                                     | _  |
| Power supply:   | 12 V DC / 1.5 A (included)   |
| Power consumption:                                    | max. 18 W  |
| Operation temp:                                       | -10 °C 45 °C   |
| Permissible relative humidity:                        | 5 % 95 % (non-condensing)  |
| Weight:   | 0.36 kg  |
| Dimensions:   | 91 x 91 x 181 mm   |
| Manufacturer / Brand:                                 | RUIJIE / REYEE   |
| Guarantee:  | 3 years  |