

## DATA SHEET

## Code: EW-485/1/1/SO UNIDIRECTIONAL OPTICAL SEPARATOR **EW-485/1/1/SO** EWIMAR



The EW-485/1/1/SO separator is designed for galvanic separation of devices connected via the RS-485 bus. It eliminates transmission interferences and possible damages to RS-485 line transmitters caused by potential differences.

Removable screw terminals are used as connecting elements. The condition of correct protection is connecting the EW-485/1/1/SO device to the proper grounding or PE wire.

Number of inputs:	1 pcs Port RS-485 1 pcs Power supply
Number of outputs:	1 pcs
Operation mode:	one-direction RS-485 : Master - Slave
Max. transmission speed:	1 Mbit
Overvoltage protection:	600 W - Port RS-485 + Power connector
Opto-isolation between input and output:	1 kV DC
Power supply:	9 V - 24 V AC/DC
Current consumption:	50 mA @ 12 V DC
Operation temp:	-20 °C 60 °C
Weight:	0.03 kg
Dimensions:	73 x 32 x 24 mm
Manufacturer / Brand:	EWIMAR
Guarantee:	2 years



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60