

DATA SHEET

Code: ATLO-AZ-WG13A-TUYA ALARM KIT ATLO-AZ-WG13A-TUYA

The ATLO-AZ-WG13A-TUYA alarm set is an ideal solution for people looking for a simple and reliable alarm system for home applications.

The device has the ability to work with the Tuya Smart application for mobile devices.

Tuya is an international home automation platform that connects thousands of products made by different manufacturers. The system can support all the most popular communication protocols such as Wi-Fi, Zigbee, Bluetooth.

Thanks to wireless communication between the system components and its simple and intuitive configuration by phone, SMS or via a mobile application, there is no need to call the installer to install the devices.

Attention! The GSM module built into the device does not support mobile data transmission.



Aspect ratios:	2.4 " TFT LCD
Number of supported wireless devices:	max. 30 pcs
Number of supported remote control keyfobs:	max. 8 pcs, In the kit : 2 pcs
The RFID cards/keyfobs support:	Unique EM 125kHz
Number of supported wireless sirens:	1 pcs
PIR detectors included:	1 pcs, Wireless
Magnetic contact included:	1 pcs, Wireless
Keyboard included:	✓
Expander included :	_
Wireless:	433 MHz
Mobile phones support:	Access by a cloud (P2P) • The <u>Tuya Smart</u> free application on Android • The <u>Tuya Smart</u> free application on iOS
Zones:	99 (wireless zones)
Timers:	¥
Users + admins:	6



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

Default administrator password:	6666
Default user password:	1234
Built-in modules:	GSM, WiFi
Access from PC:	-
Mobile phones support:	Remote control of the control panel via SMS, Tuya Smart application
Main features:	 Bidirectional communication, SMS notification about alarm and power failure, LED indication, LCD display, Built-in alarm siren - 100 dB, Alarm mute function
Supported languages:	Chinese, English, German, Russian, Spanish, Polish, Italian, French, Portuguese, Greek, Romanian
Power supply:	 5 V DC / 2 A (power adapter included) Built-in battery that maintains the control panel operation during a power failure : 3.7 V / 1000 mAh
Housing:	Plastic
Color:	Black
Operation temp:	-10 °C 55 °C
Weight:	0.2 kg
Dimensions:	185 x 125 x 14 mm
MAGNETIC CONTACT:	
Detection:	Opening the door or window
Alarm signaling:	Signal to control panel
Frequency range:	433 MHz
Alarm inputs:	-
Battery:	1 x CR2032 3V (included)
Weight:	 0.02 kg - Transmitter 0.01 kg - Magnet
Dimensions:	• 60 x 23 x 13 mm - Transmitter • 40 x 13 x 10 mm - Magnet
PIR DETECTOR:	
Battery power supply:	2 x 1.5V, type AAA/LR03 battery (included)
Frequency range:	433 MHz
Radio communication range (at open area):	max. 30 m
Detection angle / Detection range:	120 ° / 12 m (max)
Main features:	Code 1527 data encryption
Weight:	0.06 kg
Dimensions:	105 x 40 x 27 mm

REMOTE CONTROL:



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

Frequency band:	433 MHz	
Main features:	 LED indication One-touch action buttons : arm, disarm, arming only perimeter protection zones, SOS 	
Battery:	1 x CR2025 (included)	
Weight:	0.02 kg	
Dimensions:	58 x 32 x 11 mm	
NDOOR SIREN:		
Connector:	Jack 3.5 mm	
Sound pressure level:	120 dB	
Color:	White	
Weight:	0.06 kg	
Dimensions:	63.5 x 54 x 47.5 mm	
eneral information:		
Manufacturer / Brand:	ATLO	
Guarantee:	2 years	

