

Code: DS-2CD2T46G2P-ISU/SL(2.8MM)(C)

## IP CAMERA **DS-2CD2T46G2P-ISU/SL(2.8MM)(C)** PANORAMIC ACUSENSE - 4.1 Mpx 2 x 2.8 mm Hikvision

The IP camera is equipped with 2 high quality image sensors and 2 lenses with 2.8 mm focal length. Thanks to its unique design, the camera has a 180° viewing angle.

**Attention!** Camera from AcuSense series. PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Powered by Darkfighter - the camera has very good sensitivity, dedicated to poor lighting conditions.



Standard:	TCP/IP
Sensor:	2 x 1/2.5 " Progressive Scan CMOS
Matrix size:	2 x 2 Mpx - 4.1 Mpx (total)
Resolution:	3140 x 1368 - 4.1 Mpx
Lens:	2 x 2.8 mm
View angle:	180 ° (horizontal) 44 ° (vertical)
Range of IR illumination:	40 m
RS-485 interface:	—
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	1 / 1
Audio:	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Digital Noise Reduction</li> </ul>
Main stream frame rate:	25 fps @ 4.1 Mpx
Network interface:	10/100 Base-T (RJ-45)



# DATA SHEET

Memory card slot:	Micro SD memory cards up to 512GB support (possible local recording)
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">Hik-Connect</a></li><li>• iOS: Free application <a href="#">Hik-Connect</a></li></ul>
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	192.168.1.64
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	<ul style="list-style-type: none"><li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization</li><li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization</li></ul>
WEB Server:	Built-in
Max. number of on-line users:	6
ONVIF:	✓
Main features:	<ul style="list-style-type: none"><li>• Camera from AcuSense series</li><li>• WDR - 120 dB - Wide Dynamic Range</li><li>• 3D-DNR - Digital Noise Reduction</li><li>• ROI - improve the quality of selected parts of image</li><li>• NAS - Network Attached Storage support</li><li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li><li>• SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream</li><li>• Active deterrence function - Light and sound alarm</li><li>• White light (LED) illuminator built-in : 4 LEDs</li><li>• BLC - Back Light Compensation</li><li>• HLC - High Light Compensation (spot)</li><li>• AGC - Automatic Gain Control</li><li>• Possibility to change the resolution, quality and bit rate</li><li>• Configurable: brightness, contrast, saturation</li><li>• Smart motion detection (with recognizing people and vehicles)</li><li>• Intelligent Image Analysis - crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area - classification of people and vehicles, scene changing</li></ul>
Power supply:	<ul style="list-style-type: none"><li>• 12 V DC / 880 mA,</li><li>• PoE (802.3af)</li></ul>
Power consumption:	<ul style="list-style-type: none"><li>• ≤ 10.5 W @ 12 V DC</li><li>• ≤ 12.5 W @ PoE</li></ul>
Housing:	Compact, Metal
Color:	White
Vandal-proof:	—
"Index of Protection":	IP67
Operation temp:	-30 °C ... 60 °C



## DATA SHEET

Weight:	1.43 kg
Dimensions:	119 x 105 x 307 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian
SAP Code:	311320496
Manufacturer / Brand:	Hikvision
Guarantee:	<b>3 years</b>