

Code: SBW-02/ANT

## SMART GATE AND DOOR CONTROLLER **SBW-02/ANT** Wi-Fi, 12 ... 24 V AC/DC ZAMEL

The SBW-02/ANT controller enables remote opening and closing of swing gates, sliding gates, garage gates and doors. The device is enough to be attached to the gate operator or electric lock to be able to safely control gates and doors. Control is possible via a physical switch, a web browser, or the SUPLA mobile application.

To work with full functionality, the device requires connection to a home Wi-Fi network.

Voice control allows you to control the device via voice commands from Amazon Alexa or the Google Assistant (Internet access required).



|                        |                                                                                                                                                                    |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Support:               | SUPLA                                                                                                                                                              |
| Application:           | swing gates, sliding gates, garage gates, doors                                                                                                                    |
| Rated voltage:         | 12 ... 24 V AC/DC                                                                                                                                                  |
| Total maximal current: | 3 A @ 24 V AC                                                                                                                                                      |
| Number of inputs:      | 2                                                                                                                                                                  |
| Number of outputs:     | 2                                                                                                                                                                  |
| Connector type:        | screw terminals                                                                                                                                                    |
| Wireless:              | Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n                                                                                                                                 |
| Mobile phones support: | <ul style="list-style-type: none"> <li>The <a href="#">SUPLA</a> free application on Android</li> <li>The <a href="#">SUPLA</a> free application on iOS</li> </ul> |

|                        |                                                                                                                                                                                                                                                                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:         | <ul style="list-style-type: none"> <li>• Control from a Web browser,</li> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Possibility to manually program scenarios from the built-in API,</li> <li>• SMA RP connector for an external antenna</li> </ul> |
| Housing:               | Plastic                                                                                                                                                                                                                                                                                                                                                 |
| "Index of Protection": | IP20                                                                                                                                                                                                                                                                                                                                                    |
| Color:                 | Green                                                                                                                                                                                                                                                                                                                                                   |
| Operation temp:        | -20 °C ... 55 °C                                                                                                                                                                                                                                                                                                                                        |
| Weight:                | 0.039 kg                                                                                                                                                                                                                                                                                                                                                |
| Dimensions:            | 57 x 47 x 20 mm                                                                                                                                                                                                                                                                                                                                         |
| Manufacturer / Brand:  | ZAMEL                                                                                                                                                                                                                                                                                                                                                   |
| Guarantee:             | 2 years                                                                                                                                                                                                                                                                                                                                                 |