

Code: DS-2CD2366G2-ISU/SL(2.8MM)(C)

IP CAMERA **DS-2CD2366G2-ISU/SL(2.8MM)(C)** ACUSENSE 6 Mpx Hikvision

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 6 MPx.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install. Camera from AcuSense series.

Powered by Darkfighter - the camera has very good sensitivity, dedicated to poor lighting conditions. Camera is according to IP67 Index of Protection norm.



| | |
|---------------------------|--|
| Standard: | TCP/IP |
| Sensor: | 1/2.4 " Progressive Scan CMOS |
| Matrix size: | 6 Mpx |
| Resolution: | 3200 x 1800 - 5.7 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p |
| Lens: | 2.8 mm |
| View angle: | 105 ° |
| Range of IR illumination: | 30 m |
| RS-485 interface: | — |
| Memory card slot: | Micro SD memory cards up to 256GB support (possible local recording) |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| Alarm inputs / outputs: | 1 / 1 |



DATA SHEET

| | |
|--------------------------------|--|
| Audio: | <ul style="list-style-type: none">• Microphone built-in,• External microphone input,• Audio output,• Speaker built-in - Alarm siren,• Bi-directional audio streaming support |
| Main stream frame rate: | 25 fps @ 5.7 Mpx |
| Network interface: | 10/100 Base-T (RJ-45) |
| WEB Server: | Built-in |
| Max. number of on-line users: | 6 |
| ONVIF: | 18.12 |
| Main features: | <ul style="list-style-type: none">• Camera from AcuSense series• WDR - 120 dB - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• BLC/HLC - Back Light / High Light Compensation• ROI - improve the quality of selected parts of image• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect• SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its• NAS - Network Attached Storage support• Day/night mode• ICR - Movable InfraRed filter• Auto White Balance• AGC - Automatic Gain Control• Possibility to change the resolution, quality and bit rate• Sharpness - sharper image outlines• Image rotation and mirror• Configurable Privacy Zones• Motion Detection• Filtering of false alarms based on the recognition of persons and vehicles• Light and sound alarm,• Intelligent Image Analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area - classification of people and vehicles, scene changing, face detection |
| Mobile phones support: | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application Hik-Connect• iOS: Free application Hik-Connect |
| Default IP address: | 192.168.1.64 |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Web browser access ports: | 80 |
| PC client access ports: | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application |
| Mobile client access ports: | 8000 |
| Port ONVIF: | 80 |
| RTSP URL: | <ul style="list-style-type: none">• Main stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization• Sub stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization |

| | |
|------------------------|---|
| Power supply: | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 700 mA |
| Power consumption: | <ul style="list-style-type: none"> • ≤ 9.7 W @ PoE (802.3af) • ≤ 8.4 W @ 12 V DC |
| Housing: | Dome, Metal |
| Color: | White |
| "Index of Protection": | IP67 |
| Vandal-proof: | — |
| Operation temp: | -30 °C ... 60 °C |
| Weight: | 0.84 kg |
| Dimensions: | Ø 138 x 112 mm |
| Supported languages: | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 311316225 |
| Guarantee: | 3 years |