

Code: SOT-5

MOTOR UNIT DRIVER **SOT-5**

The SOT-5 motor unit driver is designed to cooperation with pan/tilt motor units and motozoom lenses. The driver executes the commands from devices with RS-485 telemetry transmitter, eg control panels, DVRs, video capture cards, video servers. The device casing is designed to outdoor mounting to a wall or to a mast with a tie.

ATTENTION! Switch the power off during cables connecting.



Number of operating motor units:	1 pcs
Camera power output:	12 V DC / 0.4 A
Current consumption in waiting mode:	50 mA
Maximal current load of directions outputs:	0.5 A
Maximal current load of ZOOM, FOCUS outputs:	0.1 A
RS-485 transmission baud rates:	2400, 4800, 9600 bps
Available protocols:	Pelco-D, Pelco-P, Delta-M
Short-circuit outputs protection:	✓
Motor unit control:	<ul style="list-style-type: none"> • right • left • down • up • right down • right up • left down • left up • autoscan
Camera control:	<ul style="list-style-type: none"> • Zoom - focal length adjustment • Focus - sharpness adjustment
Control socket type:	terminals
Power socket type:	terminals
Power supply:	24 V AC
Weight:	0.11 kg
Dimensions:	112 x 37 x 91 mm
Guarantee:	2 years