

Code: BCS-L-PIP14FW

IP CAMERA **BCS-L-PIP14FW** PINHOLE - 4 Mpx 2.8 mm BCS Line

Indoor micro camera equipped with very good quality CMOS sensor. The camera has extensive functions of intelligent image analysis.

Camera is equipped with PINHOLE type lens, needs only a very small hole to get right field of view. Camera has microphone and audio output built-in.



Standard:	IP
Resolution:	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Sensor:	1/3 " Progressive Scan CMOS
Lens:	2.8 mm @ F2.0 (pinhole)
View angle:	96 °
Range of IR illumination:	—
Memory card slot:	—
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	—



DATA SHEET

Audio:	• Audio input • Microphone built-in, • Audio output • Bi-directional audio streaming support
Main stream frame rate:	• 20 fps @ 4 Mpx • 25 fps @ 3.7 Mpx
Interface:	10/100 Base-T (RJ-45)
WEB Server:	Built-in
Max. number of on-line users:	20
ONVIF:	✓
Intelligent image analysis:	• intrusion • crossing the line (tripwire)
Main features:	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Configurable Privacy Zones • Motion Detection • AWB - Auto White Balance • AGC - Automatic Gain Control • AES - Auto Electronic Shutter • Day/night mode • ICR - Movable InfraRed filter • Mirror - Mirror image • D-ZOOM - Digital Zoom : 16 x
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Power supply:	12 V DC / 150 mA
Power consumption:	max. 1.8 W
Housing:	Mini - Metal
Color:	Black
"Index of Protection":	—
Mechanical protection class:	—



DATA SHEET

Operation temp:	-40 °C ... 60 °C
Weight:	0.08 kg
Dimensions:	• 44 x 35 x 30 mm • 50 cm (cable length)
Supported languages:	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian
Manufacturer / Brand:	BCS Line
Guarantee:	3 years