

Code: IPC-B32P-V2

IP CAMERA **IPC-B32P-V2** Wi-Fi Cell Go - 3 Mpx 2.8 mm IMOU

The cameras of the IMOU series have been designed with special care to simplify the configuration and operation. Thanks to the battery power, you can place them anywhere without any wiring problems. In combination with the user friendly IMOU platform, the IMOU series devices allow anyone to create a simple and effective surveillance system.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m.

The device is ideal for eg. as a baby monitor, with mobile image view on smartphone and possibility of bi-directional audio transmission. For outdoor use. Camera is according to IP65 Index of Protection norm.



Standard:	IP
Sensor:	Progressive Scan CMOS
Resolution:	2304 x 1296 - 3 Mpx
Lens:	2.8 mm
View angle:	98 °
Range of IR illumination:	7 m
Audio:	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in • Bi-directional audio streaming support • Alarm siren - 90 dB
Image compression method:	H.265 / H.264
Main stream frame rate:	15 fps @ 3 Mpx
ONVIF:	—
Network interface:	Wi-Fi - IEEE 802.11 b/g/n/ac - 2.4 GHz
Mobile phones support:	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application IMOU • iOS (iPhone): Free application IMOU
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	DHCP
Web browser access ports:	—

PC client access ports:	—
Mobile client access ports:	—
Port ONVIF:	—
WEB Server:	—
RTSP URL:	—
Memory card slot:	—
Internal memory:	4 GB eMMC
Main features:	<ul style="list-style-type: none"> • Wi-Fi module - IEEE 802.11 b/g/n/ac, Range : 50 m (open area), • Ability to set your own mode of operation, • VLOG mode - possibility of manual recording by pressing the button on the case, • micro USB socket • PIR detector - Built-in • People detection
Power supply:	<ul style="list-style-type: none"> • built-in battery : 5000 mAh • 5 V DC / 2 A (power adapter not included)
Power consumption:	≤ 3.5 W
"Index of Protection":	IP65
Operation temp:	-20 °C ... 50 °C
Weight:	0.207 kg
Dimensions:	88 x 60 x 41 mm (without bracket)
Supported languages:	—
Manufacturer / Brand:	DAHUA / IMOU
Guarantee:	2 years