

DATA SHEET

Code: APTI-W30S2-TUYA

PTZ OUTDOOR IP CAMERA **APTI-W30S2-TUYA** Tuya Smart Wi-Fi, - 3 Mpx 3.6 mm

The cameras cooperating with the user-friendly Tuya platform have been designed with special care to simplify the configuration process and enable the user to create a simple and effective monitoring system.

The free Tuya Smart application will send a notification to your phone when the sensors in the camera detect movement or sound, and you can control the device at any time, regardless of where you are - all you need is Internet access and a smartphone.

Tuya Smart application works perfectly with Google Assistant, Amazon Alexa and many others, which allows you to control connected devices using voice commands.

Attention! Devices cooperating with the Tuya platform do not have a WEB interface. Controlling the device and schedule settings is possible if the device has access to the Internet.



Standard:	IP
Resolution:	2304 x 1296 - 3 Mpx
Sensor:	Progressive Scan CMOS
Lens:	3.6 mm
View angle:	50 °
Range of IR illumination:	20 m
White light LED illuminator range:	20 m
Horizontal rotation range:	0 ° 350 ° Rotation of the head is limited by stops
Vertical rotation range:	0 ° 93 °
Audio:	Microphone built-in, Speaker built-in, Audio transmission via network, Bi-directional audio streaming support
Main stream frame rate:	10 fps
Network interface:	• Wi-Fi - IEEE 802.11 b/g/n, • Ethernet - 10 / 100 Mbps (RJ-45)
ONVIF:	✓





DATA SHEET

WEB Server:	-
Mobile phones support:	Access by a cloud (P2P) • The <u>Tuya Smart</u> free application on Android • The <u>Tuya Smart</u> free application on iOS
Default IP address:	DHCP
Web browser access ports:	_
PC client access ports:	-
Mobile client access ports:	-
RTSP URL:	-
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Main features:	Wi-Fi module - IEEE 802.11 b/g/n, Range : 30 m (open area) Cooperation of the Tuya Smart application with Google Assistant, Amazon Alexa RESET button
Power supply:	12 V DC
Housing:	Mini Speed Dome, Plastic
Weight:	0.311 kg
Dimensions:	160 x 145 x 100 mm
Operation temp:	-10 °C 60 °C
Supported languages:	English
Guarantee:	2 years