

Code: RG-CS83-12GT4XS-P

## SWITCH POE **RG-CS83-12GT4XS-P** 12-PORT SFP RUIJIE

Due to the reliability and ensuring high quality of transmission, the RG-CS83-12GT4XS-P 12-port PoE switch is an ideal solution for applications in CCTV IP installations. 12 ports support Power over Ethernet (PoE) function.



LAN ports:	<ul style="list-style-type: none"> <li>• 12 x RJ45 10/100/1000 Base-T ( 12 x PoE (802.3af/at) ),</li> <li>• 4 x port SFP - Uplink</li> <li>• 1 x RJ45 - Configuration possibility from PC,</li> <li>• 1 x USB - Configuration possibility from PC</li> </ul>
Management:	✓
Number of fan coolers:	1
Transmission speed:	<ul style="list-style-type: none"> <li>• 10/100/1000 Mbps : 12 LAN &amp; PoE ports Uplink ports</li> <li>• 1/10 Gbps - 4 x SFP ports</li> </ul>
Maximal total power:	370 W
Switching capacity:	104 Gb/s
Forwarding rate:	78 Mpps
MAC addresses table:	16k
Mobile phones support:	Android: <a href="#">Ruijie Reeye</a> free application iOS (iPhone): <a href="#">Ruijie Reeye</a> free application
Main features:	<ul style="list-style-type: none"> <li>• Can be mounted in a Rack cabinet</li> <li>• Switch is managed through the web and the cloud (Ruijie Reeye application)</li> <li>• Access Control List - ACL package filtering based on source and destination IP addresses</li> <li>• IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs</li> <li>• DHCP client, DHCP server, DHCP Relay support</li> <li>• Spanning Tree STP/RSTP/MSTP</li> <li>• IGMP Snooping V1/V2/V3</li> <li>• DHCP snooping support</li> <li>• Loop Protection</li> <li>• MTBF (Mean Time Between Faults) &gt; 24.14 years</li> </ul>
Certificates:	CE, RoHS
Protections:	Protection against lightning discharges : 10 kV
Housing:	Rack 19", Metal
Power supply:	100 V ... 240 AC
Power consumption:	≤ 405 W



# DATA SHEET

---

Operation temp:	0 °C ... 45 °C
Weight:	2.9 kg
Dimensions:	442 x 222 x 44 mm
Manufacturer / Brand:	RUIJIE
Guarantee:	<b>3 years</b>