DATA SHEET

Code: SCP-35-12

BUFFERED POWER SUPPLY ADAPTER **SCP-35-12**

The buffered power supply adapter is designed to powering control panels, sensors, code locks, cameras, consoles, intercoms and other alarm system equipment.
Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current. Please pay attention for proper cooling conditions of the power adaptor during work!



Adapter type:	Switching
Power voltage:	85 ... 264 V AC
Output voltage:	13.8 V DC
Output voltage adjustment:	13.1 ... 15.8 V
Maximal load:	2.6 A
Battery charging current:	0.26 A
Output power:	35 W
Efficiency:	83 %
Number of outputs:	1 pcs
Protections:	• Overvoltage • Overload protection
Operation temp. / Relative humidity:	-20 °C ... 90 °C / 20 % ... 90 %
Supported standards:	UL60950-1, TUV EN60950-1
EMI conduction and radiation:	Compliance to EN55022 (CISPR22) class B
Harmonic:	Compliance to EN61000-3-2,-3 standard

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

EMS immunity:	Compliance with EN61000-4-2, 3, 4, 5, 6, 8, 11, ENV50204, EN55024, EN61000-6-1 standards
MTBF (Mean Time Between Faults):	523300 hours
Weight:	0.35 kg
Dimensions:	99 x 98 x 36 mm
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60