

Code: AXON-POE-MULTINET

OVERVOLTAGE LIMITER **AXON-POE-MULTINET**

The AXON-POE-MULTINET is multi-channel device of AXON company designed to overvoltage protection of Ethernet 10/100 Mb/s network devices connected to it and powered remotely with PoE technology. Each of 4 PoE Multi NetProtector channels has 2 lines - the data line (pairs: 1-2, 3-6) and power line (pairs: 4-5, 7-8). To increase the load of power line the wire 4 is shorted to wire 5, and the wire 7 to 8. Using the shielded RJ-45 sockets and FTP cable you can ensure shield continuity. The socket shield is connected to the ground. The condition of correct protection is connecting the AXON-POE-MULTINET device to the proper grounding or PE wire.



Signal line - wires 1, 2, 3, 6:	
Rated voltage:	5 V
Maximal voltage:	6 V
Voltage protection level line-line:	40 V - 1 kV/μs
Voltage protection level line-PG:	600 V - 1 kV/μs
Nominal discharge current (line-line):	20 A (10/1000μs)
Nominal discharge current (line-PG):	20 A (10/1000μs)
Power line - wires 4, 5 and 7, 8:	
Nominal power voltage:	50 V
Maximal power voltage:	56 V
Nominal current:	400 mA
Voltage protection level line-line for power:	95 V - 1 kV/μs
Voltage protection level line-PG for power:	1000 V (1.2/50μs)
Nominal discharge current line-line for power:	10 A (10/1000μs)
Nominal discharge current for power (line-PG):	2 kA (8/20μs)
Protection parameters compliance:	Compliance with PN-EN61643-21
General information:	
Number of channels:	4
Sockets type:	RJ45 (8P8C)
Housing:	Metal, black



DATA SHEET

Dimensions:	167 x 50 x 32 mm
Weight:	0.33 kg
Guarantee:	2 years

