

Code: AXON-MINI/TELECOM

OVERVOLTAGE LIMITER **AXON-MINI/TELECOM** (1 + 2 OUTLETS) +TEL

The AXON-MINI/TELECOM ensures continuous protection against overvoltages of three devices and ADSL transmission line. It is equipped with one grounded power outlet, two flat non-grounded power outlets and two RJ-11 phone sockets. It is perfect solution to increase the functionality of the single surface power outlet.



Rated voltage:	230 V AC / 50 Hz
Total maximal current:	10 A
Nominal discharge current for TEL line:	2 kA (La,b/PE) - (8/20µs)
Maximal total load:	2300 W
Response time:	< 25 ns
Number of outlets:	3 outlets, two-contact 10A/250V including 1 with ground contact
TEL line maximal stroke current:	5 kA (La,b/PE) - (8/20µs)
Leak current:	< 0.5 mA
Nominal voltage of surge suppressor:	250 V / 50 Hz
Protection level of surge suppressor:	≤ 1.3 kV (L/N)
Nominal stroke current:	2 kA (L/N) - (8/20µs)
ADSL TELEPHONE LINE:	
Phone sockets type:	RJ11 (6P4C)
Protected wires of ADSL line:	2 z 4
Maximum stroke current:	6.5 kA (L/N) - (8/20µs)
Rise time of surge suppressor for TEL line:	≤ 25 ns
Nominal voltage of surge suppressor for TEL line:	150 V



DATA SHEET

Level of surge protection for TEL line:	≤ 1 kV (La,b/PE)
Electric shock protection system:	Ground connectors (pins) connected with ground wire of AC mains
Housing:	Plastic - non-flammable
Dimensions:	131 x 55 x 75 mm
Weight:	0.13 kg
Guarantee:	2 years