

Code: TRVGA-300-P

EXTENDER VGA **TRVGA-300-P**

The TRVGA-300-P is designed for active transmission of the VGA signal via twisted-pair cable for the distance up to 300m. The transmitter converts the VGA signal, what enables its transmission via twisted-pair cable. Three pairs of wires allow to RGB signals transmission, the fourth pair - the synchronization of the transmission.

The device is equipped with overvoltage protection of the symmetrical line. The transmitter and receiver are sold as a set and a both devices need to be used for complete channel transmission.

Transmitter and receiver are in the kit.



Device type:	Active / Transmitter
Number of channels:	1 VGA
Power supply:	12 V / 70 mA (power adapter not included)
Video transmission range:	max. 300 m
Symmetrical socket impedance:	100 Ω
Connectors type:	VGA Socket
Symmetrical socket type:	RJ-45 (8-pin, 4 pairs) Socket
Weight:	0.078 kg
Dimensions:	118 x 30 x 48 mm
Device type:	Active / Receiver
Number of channels:	1 VGA
Power supply:	12 V / 170 mA (power adapter not included)
Video transmission range:	max. 300 m
Symmetrical socket impedance:	100 Ω
Connectors type:	VGA Socket female
Symmetrical socket type:	RJ-45 (8-pin, 4 pairs) Socket
Weight:	0.078 kg
Dimensions:	118 x 30 x 54 mm
Main features:	• Short-circuit protection • Signal correction
Resolution:	• 1920 x 1200 / 80 Hz @ 100 m • 1024 x 768 / 60 Hz @ 300 m



DATA SHEET

Manufacturer / Brand:	DELTA
Guarantee:	3 years