

Code: TL-WR743ND

## ACCESS POINT +ROUTER **TL-WR743ND** 150 Mbps

The TL-WR743ND combines access point, broadband router (for xDSL or cable modem), and 4-port FastEthernet switch.

The device is an integrating router, firewall and access point. Additionally it can operate in WISP mode (wireless client).

This is a very useful feature if the ISP offers Internet access via wireless connection. Main applications include Internet accesses in small and medium size businesses, SOHO, and homes.

The TL-WR743ND enables the user to quick and easy create a wireless network and share the Internet connection to many computers and the built-in firewall additionally protects the network.

The TL-WR743ND ensures advanced access control and NAT, its DHCP server supports static assignment of IP addresses. The device also supports virtual servers, DMZ zone, remote logging and management.



Frequency range:	2.4 GHz ... 2.4835 GHz
Antenna type:	5 dBi dipole SMA R/P Possibility to add an external antenna
Standards:	IEEE 802.11 b/g/n
Baud rates:	150 Mbps
CPU:	Atheros
Modulation type:	CCK, OFDM
Ethernet interface:	1 x 10/100 Mbps (RJ-45)
LED indicators:	Power, System, LAN, WLAN, Act/Link (4 x Ethernet)
Min. illumination:	<ul style="list-style-type: none"> <li>• 130M: -68dBm@10% PER</li> <li>• 108M: -68dBm@10% PER</li> <li>• 54M: -68dBm@10% PER</li> <li>• 11M: -85dBm@8% PER</li> <li>• 6M: -88dBm@10% PER</li> <li>• 1M: -90dBm@8% PER</li> </ul>
DDNS:	<ul style="list-style-type: none"> <li>• No-IP</li> <li>• DynDNS</li> <li>• Comexe</li> </ul>
DHCP server:	✓



# DATA SHEET

Firmware update:	✓
Operation mode:	AP router, WISP router + AP
Protections:	64/128/152-bit WEP, WPA/WPA2, TKIP/AES Table of access / access-deny according to MAC addresses of client cards Internet access filtering via filters of IP addresses, MAC addresses and ports of TCP/IP protocol
Number of LAN ports:	4 x 10/100 Mbps (RJ-45. UTP/STP)
Management interface:	Web browser
Transmitter power:	max. 20 dBm
Power supply:	9 V DC / 600 mA (power adapter included)
Operation temp. / Relative humidity:	0 °C ... 50 °C / 95 % (non-condensing)
Main features:	<ul style="list-style-type: none"><li>• MAC address cloning</li><li>• Firewall</li><li>• Internet access filtering</li><li>• Static / dynamic routing</li><li>• Built-in 4-port switch</li></ul>
Weight:	0.170 kg
Dimensions:	174 x 121 x 34 mm
Guarantee:	2 years