

Code: FLEX-1642

NVR **FLEX-1642** 20 CHANNELS



Standard:	TCP/IP
Supported resolutions:	4 @ 2048 x 1536 px, 16 @ 1920 x 1080 px, 20 @ 1280 x 960 px, 20 @ 1280 x 720 px, 8 @ 1920 x 1080 px in the same time with: 8 @ 1280 x 960 px
Audio support:	20 Channels
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	Audio from cameras
Audio outputs:	1 pcs BNC
Image compression method:	H.264
Maximal total frame rate:	500 fps @ 1280 x 960 px, 500 fps @ 1280 x 720 px, 400 fps @ 1920 x 1080 px, 100 fps @ 2048 x 1536 px,
Supported hard drives:	2 x 4 TB SATA

Operation modes:	Firmware V4.0[20150616] : • 20 x Main stream (1280 x 960) + 20 x Sub stream (640 x 480) + 4 Channels played simultaneously • 20 x Main stream (1280 x 960) + 20 x Sub stream (720 x 576) + 4 Channels played simultaneously • 16 x Main stream (1280 x 960) + 16 x Sub stream (640 x 480) + 4 Channels played simultaneously • 16 x Main stream (1920 x 1080) + 16 x Sub stream (640 x 480) + 4 Channels played simultaneously • 16 x Main stream (1280 x 960) + 16 x Sub stream (720 x 576) + 4 Channels played simultaneously • 16 x Main stream (1920 x 1080) + 16 x Sub stream (720 x 576) + 4 Channels played simultaneously • 16 x Main stream (1280 x 960) + 16 x Sub stream (720 x 576) + 4 Channels played simultaneously • 9 x Main stream (1920 x 1080) + 9 x Sub stream (960 x 576) + 4 Channels played simultaneously • 8 x Main stream (1920 x 1080) + 8 x Main stream (1280 x 960) + 16 x Sub stream (640 x 480) + 4 Channels played simultaneously • 4 x Main stream (2048 x 1536) + 4 x Sub stream (960 x 576) + 4 Channels played simultaneously • 4 x Main stream (1920 x 1080) + 8 x Main stream (1280 x 960) + 12 x Sub stream (960 x 576) + 4 Channels played simultaneously
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	ONVIF, I8, I9, RTSP
External storage devices backup:	Records backup at .mp4 / .avi format to USB (pendrive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Network functions:	Live image view, Playback the records, Backup the records
Bitrate:	16 ... 8000 kbps
ONVIF:	✓
Mobile phones support:	Port 5053 • Android: Free application MEye • iOS (iPhone): Free application Meye • Windows Phone: Free application Meye Access by a cloud (P2P) • Android: Free application Goolink • iOS (iPhone): Free application Goolink
Alarm inputs / outputs:	4 / 2
Operation temp:	-10 °C ... 55 °C
PTZ control:	RS-485 - PELCO-D/P
Motion Detection:	22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 3 A (power adapter included)
Weight:	1.72 kg
Dimensions:	360 x 244 x 44 mm
Supported languages:	English, Polish



DATA SHEET

Country of origin:	China
Guarantee:	2 years