

DATA SHEET

Code: VMT-172

MONITOR VGA, 2xVIDEO, HDMI, AUDIO VMT-172 17 " VILUX

CCTV monitor in plastic housing. Due to its picture ratio 4:3, this monitor is perfect solution for monitoring applications, because there is a natural image ratio (image is not horizontally scaled up). The LED matrix illumination technology allows to real colors reproduction, 40% lower current consumption and much lower failure rate compared to normal LCD monitors with CCFL illumination.

Monitor is perfect solution to work with PC, where there is a need to view the image from DVR in the same time. This model is equipped with all kinds of inputs, what allows to display an image from any kind of signals using in CCTV systems.

Interesting solution is placing the speakers of the back side of housing. It does not bother listening to the AUDIO from the recorder at the same time does not reduce the area of the monitor front panel.

The device is designed to continuous work in closed spaces.



Screen size:	17 "
Native resolution:	1280 x 1024 px
Aspect ratios:	5:4
Matrix type:	TFT-LCD color matrix - Matte matrix
Matrix backlight:	In LED technology
Supported standards:	PAL/NTSC
Contrast:	600 : 1
Brightness:	300 cd/m ²
Viewable angles:	160 ° horizontal 140 ° vertical
Response time:	8 ms
Speakers built-in:	2 x 3 W



DATA SHEET

Signal connectors:	Composite Video (BNC) sockets: 2x in, 1x out 1x VGA 1x HDMI Audio: 1x Jack (for VGA) 2x Cinch L/R (for Video 1/2)
Housing type:	Plastic
Monitor mounting standard:	VESA 75
Power supply:	12 V DC / 3 A (power adapter included)
Power consumption:	< 40 W (operation) < 1 W (Standby mode)
Monitor control:	OSD - by monitor control keys
Operation temp:	-10 °C 60 °C
Weight:	3.42 kg
Dimensions:	390 x 350 x 210 mm (with stand) 390 x 316 x 58 mm (without stand)
Supported languages:	Polish, English, Chinese, French, Spanish, German, Portuguese, Russian, Italian
Manufacturer / Brand:	VILUX
Guarantee:	2 years