

Code: WS-6933

SATELLITE METER **WS-6933**

The WS-6933 satellite meter allows to quick set the satellite dish signal. The WS-6933 is equipped with readable menu, which helps to operate for each installer. The device has implemented over a dozen satellite positions (satellites + transponders).

The WS-6933 model allows to DVB-S2 signals measurement.

Attention! The built-in compass is too inaccurate to correctly determine the direction.



Output and input:	— / F socket
Frequency range:	950 MHz ... 2150 MHz
Signal level:	-65 ... -25 dBm
LNB power supply:	13/18 V, max. 300 mA
Switching between bandwidths:	22 kHz
DiSEqC:	1.0, 1.1
Modulation:	QPSK, 8PSK, 16APSK
Symbol rate:	2 ... 45 Msps
SCPC and MCPC support:	✓
Programming and firmware upgrade:	via USB port
Battery power supply:	Li-Ion battery 800 mAh Power adapter 12 V / 1 A (power adapter included)
Display:	240 x 320 " TFT LCD



DATA SHEET

Main features:	• Sound signaling • DiSEqC and 22kHz control support • DVB-S signals measurement / DVB-S2 - SD and HD quality channels • Flashlight built-in
Weight:	0.33 kg
Dimensions:	172 x 85 x 42 mm
Guarantee:	2 years