

Code: BCS-TIP4300AIR

IP CAMERA **BCS-TIP4300AIR** - 3.0 Mpx, 1536p 3.6 mm

IP camera equipped with very good high resolution sensor. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition.

Very easy operation by Internet Explorer browser allows the users to convenient and remote support, and also remote management of the camera. Included camera software enables management and integrated monitoring of many network cameras.



Standard:	TCP/IP
Sensor:	1/3 " Progressive Scan Aptina CMOS
Digital Image Processor:	DSP AMBARELLA
Matrix size:	3.0 Mpx
Resolution:	2048 x 1536 - 3.0 Mpx, 1536p , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Scanning system:	Progressive
Lens:	3.6 mm
View angle:	67 °
S/N ratio:	> 50 dB (AGC off)
Range of IR illumination:	30 m
Image compression method:	H.264 / MJPEG
Bitrate:	32 ... 8192 kbps - H.264 32 ... 12288 kbps - MJPEG
Main stream frame rate:	20 fps - 3.0 Mpx 25 fps - 1080p 25 fps - 720p
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	HTTP, HTTPS, TCP/IP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS,PPPOE, UPNP, NTP
WEB Server:	Built-in, NVR compliance

Max. number of on-line users:	10
ONVIF:	2.0
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS • Windows Phone: Free application wDMSS Lite There are also paid versions of mobile applications: gDMSS Plus, iDMSS Plus, wDMSS plus
RS-485 interface:	—
Alarm inputs / outputs:	—
Main features:	• DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • BLC - configurable Back Light Compensation • WB - White Balance (ATW/AWB/manual/indoor/outdoor) • Day/Night mode (color/b&w/auto) • Motion Detection • Configurable Privacy Zones - Mirror - Mirror image
Power supply:	• PoE (802.3af) • 12 V DC / 260 mA
Housing:	Metal
Color:	White / Black
"Index of Protection":	IP66
Operation temp:	-30 °C ... 50 °C
Weight:	0.53 kg
Dimensions:	177 x 70 x 70 mm
Manufacturer / Brand:	BCS
Guarantee:	2 years