

Code: BCS-NVR04015ME-P

NVR **BCS-NVR04015ME-P** 4 CHANNELS + 4-PORT POE SWITCH



Standard:	TCP/IP
Supported resolutions:	4 @ 2560 x 1920 px, 4 @ 2048 x 1536 px, 4 @ 1920 x 1080 px, 4 @ 1280 x 720 px, 4 @ 704 x 576 px
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio support:	Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264 / MPEG-4
Maximal total frame rate:	100 fps @ 2560 x 1920 px, 100 fps @ 2048 x 1536 px, 100 fps @ 1920 x 1080 px, 100 fps @ 1280 x 720 px, 100 fps @ 704 x 576 px
Supported hard drives:	1 x 4 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
Bitrate:	max. 80 Mbps
Network protocols:	HTTP, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server ONVIF
External storage devices backup:	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow All channels synchronous playback, Smart Search function
Network functions:	Full support via network, Remote records copying, Web Server built-in max. 20 on-line users

ONVIF:	2.0
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS • Windows Phone: Free application wDMSS Lite There are also paid versions of mobile applications: gDMSS Plus, iDMSS Plus, wDMSS plus
Alarm inputs / outputs:	—
PTZ control:	BCS (PTZ IP) cameras only
Motion Detection:	22 x 18 motion zones 6 sensitivity levels
Mouse support:	✓
IR remote controller in the set:	—
Switch PoE:	4-port PoE Switch built-in Cooperation with cameras with DHCP function activated
Power supply:	48 V DC / 1.5 A (power adapter included)
Weight:	0.53 kg
Dimensions:	205 x 205 x 44 mm
Supported languages:	Polish, English
Country of origin:	China
Manufacturer / Brand:	BCS
Guarantee:	2 years