

Code: SF-DVB-T

DVB-T/DVB-T2 SIGNAL METER **SF-DVB-T**

The SF-DVB-T allows to measure the TV signals at DVB-T, DVB-T2 installations. Readable menu will help the operation for any installer.



Output and input:	2 pcs F socket
Frequency range:	170 MHz ... 230 MHz (VHF), 470 MHz ... 862 MHz (UHF)
Bandwidth:	6 / 7 / 8 MHz
Demodulation:	• Constellation - DVB-T : QPSK / 16-QAM / 64-QAM - DVB-T2 : QPSK / 16-QAM / 64-QAM / 256-QAM • FEC - DVB-T : 1/2, 2/3, 3/4, 5/6, 7/8 - DVB-T2 : 1/2, 3/5, 2/3, 3/4, 4/5, 5/6
Power supply:	• 13 V DC / max. 150 mA (power adapter included) • External battery 12 V (not included)
Pre-amplifiers powering:	5 V DC
Main features:	• Channel edition - displays information such as the level and quality of the received channel, • Analysis of the spectrum for the whole frequency band, • Ability to add new channels (channel name, frequency, band)
Operation temp:	-10 °C ... 50 °C
Weight:	0.145 kg
Dimensions:	154 x 77 x 29 mm
Supported languages:	English, Polish
Guarantee:	2 years