

Code: ATLO-KRM-822

## CODE LOCK **ATLO-KRM-822**



Outdoor, autonomous code lock with RFID reader.

Autonomous operation of the device allows the user to:

- Open by using a card or PIN code.
- Remember stored cards or PIN codes.
- Signaling left the door open.
- Acoustic and optical signaling.

Administrator capabilities are following:

- Programming by using the keypad.
- Adding a new card by using the keypad.
- Adding a new card and entering a PIN code.
- Changing the PIN code of the user.
- Deleting the PIN code of the user.
- Setting the lock release time.
- Restoring the default settings.

|                                |                                                                                                                                                                                                                                                                                                                                    |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cards support:                 | Unique EM 125kHz                                                                                                                                                                                                                                                                                                                   |
| Reading distance of prox-keys: | max. 6 cm                                                                                                                                                                                                                                                                                                                          |
| Autonomous operation:          | ✓                                                                                                                                                                                                                                                                                                                                  |
| Keyboard built-in:             | ✓                                                                                                                                                                                                                                                                                                                                  |
| Doorbell button:               | ✓                                                                                                                                                                                                                                                                                                                                  |
| Tamper output:                 | ✓                                                                                                                                                                                                                                                                                                                                  |
| Power supply:                  | 12 V DC $\pm$ 10%                                                                                                                                                                                                                                                                                                                  |
| Maximal current consumption:   | 85 mA                                                                                                                                                                                                                                                                                                                              |
| Main features:                 | <ul style="list-style-type: none"> <li>• 2000 indexed users</li> <li>• Identification: Card and/or PIN</li> <li>• Blue backlight of the keys</li> <li>• Support for door contact and exit button</li> <li>• NO/NC output</li> <li>• Possible connection of the external ATLO-R series reader (read in/out door control)</li> </ul> |
| Operation temp:                | -45 °C ... 60 °C                                                                                                                                                                                                                                                                                                                   |
| Permissible relative humidity: | 10 ... 90 % (non-condensing)                                                                                                                                                                                                                                                                                                       |
| "Index of Protection":         | IP68                                                                                                                                                                                                                                                                                                                               |



## DATA SHEET

|                       |                        |
|-----------------------|------------------------|
| Housing:              | Metal - Narrow profile |
| Color:                | Silver / Black         |
| Weight:               | 0.4 kg                 |
| Dimensions:           | 44 x 150 x 29 mm       |
| Manufacturer / Brand: | ATLO                   |
| Guarantee:            | <b>3 years</b>         |

