

DATA SHEET

Code: VMT-071 MONITOR 2xVIDEO VMT-071 7 " VILUX



CCTV monitor in plastic housing. The LED matrix illumination technology allows to real colors reproduction, 40% lower current consumption and much lower failure rate compared to normal LCD monitors with CCFL illumination.

The device is designed to continuous work in closed spaces.

Screen size:	7 "
Native resolution:	800 x 480 px
Aspect ratios:	16:10
Matrix type:	TFT-LCD color matrix
Matrix backlight:	In LED technology
Supported standards:	PAL/NTSC
Contrast:	500 : 1
Brightness:	250 cd/m ²
Viewable angles:	140 ° horizontal 120 ° vertical
Response time:	25 ms
Speakers built-in:	-
Signal connectors:	Composite Video (BNC) sockets: 2x in
Housing type:	Plastic
Monitor mounting standard:	Monitor bracket with adjusted tilt in range 90 $^{\circ}$
Power supply:	12 V DC / 1 A (power adapter included)



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

Power consumption:	max. 10 W (operation) < 1 W (Standby mode)
Monitor control:	OSD - by monitor control keys
Main features:	• Auto Picture Adjustment
Operation temp:	-10 °C 50 °C
Weight:	0.48 kg
Dimensions:	178 x 119 x 95 mm (with stand) 178 x 119 x 25 mm (without stand)
Supported languages:	English, Chinese Simplified, French, Spanish, German, Polish, Portuguese, Russian, Italian
Manufacturer / Brand:	VILUX
Guarantee:	2 years

