

DATA SHEET

Code: MK-6.0/CT ALUMINUM TRUSS MAST MK-6.0/CT

The MK-6.0/CT mast is a solid, lightweight aluminum construction with the possibility of entering it by a qualified installer.

No need for guy-wires makes the mast requires little space and has a beneficial effect on aesthetics.

The mast is designed for mounting light devices such as CCTV cameras, Wi-Fi, LTE antennas or small radio links in the first wind zone (according to EUROCODE standards for Poland). The technical calculations available in the downloads are only a reference for designers. The accompanying documentation should not be considered as installation guidelines.

In the case of less typical installation locations and loads, we encourage you to contact us to verify your needs in technical terms.

Height of the mast:	6.0 m
Number of sections:	4
Wall thickness:	1.5 mm
Material:	Aluminum
Construction:	Truss of triangular cross-section : 250 \times 250 \times 250 mm
Supporting pillars:	Aluminum tube Ø 35 mm
Main features:	 The lack of guy-wires The MK-1.5/POD base application enables laying a mast Possibility of entering the assembled mast by the person weighing up to 100 kgs with winds up to 5 m/s The possibility of transport in the trunk of a passenger car The dimensions of the product after packing enable to send it by courier across Europe
Weight:	 20.2 kg - Mast 3.01 kg - Mast base 1.6 kg - Anchor for concrete
Guarantee:	2 years



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60 ALK NAVANA NAVANA