

Code: CDV70-2812

VANDALPROOF CAMERA **CDV70-2812** STANDARD: PAL, 700 TVL 2.8 ... 12 mm

Camera equipped with perfect very high resolution Sony sensor and Sony Effio Digital Image Processor.
Housing construction allows to mount the camera to the ceiling and the wall (image is right oriented in both cases). Camera module is mounted inside the dome housing, which allows to rotate the camera on any axis.
Camera is according to IP65 Index of Protection norm.



Standard:	PAL
Sensor:	1/3 " Sony ICX811AK
Digital Image Processor:	DSP Sony Effio-E
Resolution:	700 TVL
Lens:	2.8 ... 12 mm, 2 Mpx
Min. illumination:	0.001 Lux
View angle:	• 81 ° ... 23 ° (manufacturer data) • 80 ° ... 30 ° (our tests result)
Video output:	1 Vpp / 75 Ω
S/N ratio:	> 52 dB
Vandal-proof:	✓
Main features:	• 2-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • WDR - Wide Dynamic Range • Max. 4 privacy zones • Day/night mode - manual/auto • White Balance - ATW/Manual • Sharpness - sharper image outlines • Mirror - horizontal
Power supply:	12 V DC / 110 mA
OSD menu:	✓
"Index of Protection":	IP65



DATA SHEET

Housing:	Dome - Metal
Color:	White
Permissible relative humidity:	max. 95 %
Operation temp:	-10 °C ... 50 °C
Weight:	0.575 kg
Dimensions:	Ø 138 x 100 mm
Guarantee:	2 years

