

Code: SF-4

## SATELLITE METER **SF-4**

The SF-4 satellite meter allows to quick set the satellite dish signal. The SF-4 is equipped with readable menu, which helps to operate for each installer. The device has implemented a few satellite positions (satellites + transponders).

The SF-4 model allows to DVB-S2 signals measurement.



Output and input:	F socket
Frequency range:	950 MHz ... 2150 MHz
Signal level:	-65 ... -25 dBm
LNB power supply:	13/18 V, max. 500 mA
Switching between bandwidths:	22 kHz
DiSEqC:	1.0
Modulation:	QPSK, 8PSK
Symbol rate:	1 ... 45 Msps
Power supply:	<ul style="list-style-type: none"> <li>• 10 x 1.5 V AA (Batteries) (not included)</li> <li>• 13 V / 18 V SAT RECEIVER</li> <li>• 13 V ... 18 V DC from power adapter (not included)</li> </ul>
Display:	2.7 " LCD - with light indication
Main features:	<ul style="list-style-type: none"> <li>• DVB-S / DVB-S2 signals measurement - SD and HD quality channels</li> <li>• Digital meter of signal level and quality ( % )</li> <li>• Sound signaling</li> <li>• DiSEqC and 22kHz control support</li> </ul>
Weight:	0.15 kg
Dimensions:	154 x 78 x 29 mm
Guarantee:	2 years