

DATA SHEET

Code: ROCKET-M5 BASE STATION **ROCKET-M5** UBIQUITI

The ROCKET-M5 is characterized by very high efficiency combined with high output power and increased sensitivity of the receive path. The result is very long radio transmission range (even above 50 km) together with huge transmission rate of the 802.11n standard (it is 150+ Mbps real TCPI/IP). The device is designed to implement high-performance P2P radio bridges especially needed in systems using the AirMax base stations.

The AirMax system devices: bridges, base stations and antennas are designed specifically to work together.

Enominanty range.	5470 MUz 5925 MUz
Frequency range:	5470 MHz 5825 MHz
Standards:	• IEEE 802.11a, • IEEE 802.11n
LAN ports:	1 x 10/100 Mbps
Antenna connector:	2 x RP-SMA
Receiver sensitivity:	 -94 dBm @ 6 24 Mbps -80 dBm @ 36 Mbps -77 dBm @ 48 Mbps -75 dBm @ 54 Mbps
Operating system:	AirOS, AirMAX
Operation modes:	Station, Access Point
Transmitter power:	 27 dBm @ 6 24 Mbps 25 dBm @ 36 Mbps 23 dBm @ 48 Mbps 22 dBm @ 54 Mbps
Memory:	128 MB SDRAM, 8 MB FLASH
Processor:	MIPS 74Kc
Power supply PoE:	¥



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

ROCKET-M5

At

rachert

II.



DATA SHEET

Power supply:	24 V / 1 A (power adapter included)
Power consumption:	max. 8 W
Operation temp:	-30 °C 75 °C
Permissible relative humidity:	5 % 95 %
Main features:	 Available services: Web Server, SNMP, SSH Server, Telnet, Ping, Watchdog, DHCP, NAT, Bridging, Routing Antenna Alignment Tool Distance Adjustment Gain adjustment WPA2 AES Statistical Reporting Traffic Shaping WMM support (QoS mechanism of the 802.11e standard)
Support:	with antenna : • Rocket Dish 5G-30 • AirMax Sector 5G-17-90 • AirMax Sector 5G-16-120 • AirMax Sector 5G-20-90 • AirMax Sector 5G-19-120
Weight:	0.222 kg
Dimensions:	172 x 84 x 36 mm
Manufacturer / Brand:	UBIQUITI
Guarantee:	2 years



ROCKET-M5