

Code: UNIFI-LR

ACCESS POINT **UNIFI-LR** UBIQUITI

The UBIQUITI UNIFI-LR is a device working in 2x2 MIMO (Multiple Input Multiple Output) standard. The UNIFI-LR (Long Range) provides almost about 50% greater range in comparison to standard UniFi solution. The device is easy to use and manage. The distinguishing feature of the product is additional software UniFi WiFi Enterprise System, which enables configuration and management of the UniFi devices network, from computer via a web browser.



Frequency range:	2412 MHz ... 2462 MHz
Antenna type:	2Tx 2Rx MIMO 3 dBi Integrated Omnidirectional antenna
Standards:	• IEEE 802.11b • IEEE 802.11g • IEEE 802.11n
Baud rates:	300 Mbps
Wireless transmission range:	183 m
Protections:	WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
Ethernet interface:	10/100 Mbps BASE-TX (Cat. 5, RJ-45)
Operating system:	UniFi WiFi Enterprise System
Transmitter power:	max. 27 dBm
Max. power consumption:	6 W
Power supply PoE:	12 ... 24 V Ubiquiti Passive PoE
Power supply:	24 V / 0.5 A included

Main features:	• Possibility to mount on the wall or ceiling • UniFi WiFi Enterprise System • AP placement and RF maps • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions
Operation temp. / Relative humidity:	-10 °C ... 70 °C / 5 % ... 80 %
Weight:	• 0.29 kg • 0.43 kg (with mounting kits)
Dimensions:	Ø 200 x 36.5 mm
Manufacturer / Brand:	UBIQUITI
Guarantee:	2 years