

Code: DS-7604NI-E1/4P/A

NVR **DS-7604NI-E1/4P/A** 4 CHANNELS + 4-PORT POE SWITCH Hikvision

The DS-7604NI-E1/4P/A digital recorder is a professional device using in IP surveillance systems. The H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.



Standard:	TCP/IP
Supported resolutions:	max. 6 Mpx - 3072 x 2048 px
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio support:	4 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264 / H.264+
Supported hard drives:	1 x 6 TB SATA
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP, HTTPS
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Default admin user / password:	admin / -
Default IP address:	192.168.1.64
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
RTSP URL:	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream

Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Bitrate:	max. 40 Mbps
Network functions:	Live image view, Playback the records, Backup the records max. 32 on-line users - iVMS-4200 application
ONVIF:	✓
Switch PoE:	4-port PoE Switch built-in - 802.3af/at
USB:	1 pcs USB 2.0
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect
Alarm inputs / outputs:	4 / 1
PTZ control:	IP Speed Dome Cameras
Main features:	Intelligent Image Analysis - detection line violation and intrusion in an area previously designated - Hikvision only
Motion Detection:	✓
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	48 V DC / 1.36 A (power adapter included)
Operation temp:	-10 °C ... 55 °C
Weight:	1.2 kg
Dimensions:	315 x 240 x 48 mm
Supported languages:	English, Polish
Country of origin:	China
SAP Code:	303601830
Manufacturer / Brand:	Hikvision
Guarantee:	3 years