

Code: SM-800

SATELLITE METER **SM-800**

The SM-800 satellite meter allows to quick set the satellite dish signal. The SM-800 is equipped with readable menu, which helps to operate for each installer. The device has implemented over a dozen satellite positions (satellites + transponders).

The SM-800 model allows to DVB-S2 signals measurement.



Frequency range:	950 MHz ... 2150 MHz
Signal level:	35 dBμV ... 90 dBμV
LNB power supply:	13/18 V, max. 500 mA
Switching between bandwidths:	0 / 22 kHz
DiSEqC:	DiSEqC 1.0, 1.1, 1.2, USALS systems support
Power supply:	• Li-Ion battery • Power adapter 12 V / 1 A (power adapter included)
Display:	2.1 " TFT LCD - with light indication
Modulation:	QPSK, 8PSK

Main features:	• DVB-S / DVB-S2 signals measurement - SD and HD quality channels • Spectrum measurement mode • Calculation of azimuth and elevation angle • DiSEqC 1.0, 1.1, 1.2, USALS systems support • Digital meter of signal level and quality • Signal level is expressed in dBμV, and quality in % • Ability to choose between Ku / C bands • Sound signaling • Constellation diagram • Ability to edit transponders data • Measurement of C/N, S/N, BER
Weight:	0.22 kg
Dimensions:	178 x 81 x 35 mm
Guarantee:	2 years