

Code: DS-7608NI-E2/A

NVR **DS-7608NI-E2/A** 8 CHANNELS Hikvision

The DS-7608NI-E2/A digital recorder is a professional device using in IP surveillance systems. The H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.



Standard:	TCP/IP
Supported resolutions:	8 @ 5 Mpx , 8 @ 3 Mpx , 8 @ 1920 x 1080 px, 8 @ 1600 x 1200 px, 8 @ 1280 x 720 px, 8 @ 704 x 576 px
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio support:	8 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Maximal total frame rate:	200 fps @ 5 Mpx , 200 fps @ 3 Mpx , 200 fps @ 1080p , 200 fps @ 1600 x 1200 px , 200 fps @ 720p , 200 fps @ 704 x 576 px
Supported hard drives:	2 x 4 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
Network protocols:	TCP, UDP, RTP, DHCP, DDNS, SMTP, NTP, PPPoE, SADP, SNMP, NFS, iSCSI, UPnP, IPv6, ONVIF, PSIA, RTSP
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Bitrate:	max. 80 Mbps
Network functions:	Live image view, Playback the records, Backup the records max. 128 on-line users - iVMS-4200 application
ONVIF:	✓



DATA SHEET

Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect
Default admin user / password:	admin / -
Default IP address:	192.0.0.64
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
Operation temp:	-10 °C ... 55 °C
RTSP URL:	• rtsp://user:password@192.0.0.64:554/Streaming/Channels/channel_no02/ - Main stream • rtsp://user:password@192.0.0.64:554/Streaming/Channels/channel_no01/ - Sub stream
Alarm inputs / outputs:	4 / 1
PTZ control:	IP PTZ cameras
Motion Detection:	✓
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 3.33 A (power adapter included)
Weight:	1.60 kg
Dimensions:	380 x 290 x 51 mm
Supported languages:	English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Polish, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	Hikvision
SAP Code:	303601822
Guarantee:	3 years