

Code: STH-50W-4K\*P5

## LED FLOODLIGHT **STH-50W-4K\*P5** SonneTech

Illuminator can be used indoors and outdoors. Incomparably greater lifetime of the LEDs compared to traditional halogen bulb provides cheap and reliable operation.

The use of multiple LEDs provides a better heat dissipation, and the longer lifetime of the reflector and allows for uniform light output.



| In package:                        | 5 pcs The price for package       |
|------------------------------------|-----------------------------------|
| Luminous flux:                     | 4500 lm                           |
| Illumination angle:                | 120 °                             |
| Light color:                       | Neutral, 4000 ... 4500 K          |
| Twilight switch:                   | —                                 |
| Power supply:                      | 110 ... 240 V AC                  |
| Nominal power:                     | 50 W<br>53.6 W (our tests result) |
| Power factor:                      | 0.95                              |
| Power supply adapter efficiency:   | 84 %                              |
| Energy class:                      | A+                                |
| Illuminance in the distance of 3m: | 204 lx                            |
| CRI:                               | > 70                              |

|                        |                                                                                                                                   |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Main features:         | <ul style="list-style-type: none"><li>• LED SMD 5730 diodes</li><li>• LED lifetime 35 000 h</li><li>• Solid workmanship</li></ul> |
| Housing:               | Aluminum                                                                                                                          |
| "Index of Protection": | IP65                                                                                                                              |
| Operation temp:        | -20 °C ... 50 °C                                                                                                                  |
| Weight:                | 1.83 kg                                                                                                                           |
| Dimensions:            | 257 x 259 x 122 mm                                                                                                                |
| Manufacturer / Brand:  | SonneTech                                                                                                                         |
| Guarantee:             | 2 years                                                                                                                           |